

PRODUCT DATA SHEET

Sika® Stop GREEN

LONG LASTING PROTECTION AGAINST GREEN GROWTH

PRODUCT DESCRIPTION

Sika® Stop GREEN is a ready-to-use algae and mould treatment, which gradually eliminates the green growth and prevents its reappearance. It is easy to apply and does not require rinsing. Suitable for use on a variety of surfaces.

USES

For removing green stains from:

- Houses: façade walls, roofs, terraces, balconies, outside stairs.
- Gardens: paving, walkways, fences, walls, basins, statues, balusters and reservoirs without fish, etc.
- Leisure facilities: tennis courts, boat hulls, caravans and more.

CHARACTERISTICS / ADVANTAGES

- Can be applied horizontally or vertically.
- Easy application, without rinsing.
- Can be applied on all substrates: slate, shingle, stone, brick, concrete, mortar, fibre-cement, plaster, ceramic, polyester, zinc, painted surfaces, etc.
- Does not leave marks on materials.
- Curative and preventive effect.
- Can be painted or coated once the green stains have been removed.
- On painted surfaces, carry out a preliminary test and wait 72 hours (minimum) to observe the result (check that the paint is not discoloured).

PRODUCT INFORMATION

| | |
|---------------------------|--|
| Chemical Base | Quaternary ammonium in aqueous phase. |
| Packaging | 5 L and 20 L cans 1 L and 5 L sprayers |
| Colour | Ready-to-use, colourless and odourless liquid. |
| Shelf Life | 3 years in unopened original packaging. |
| Storage Conditions | Protect from frost and heat. |
| Density | approx. 1 g/cm ³ |
| pH-Value | approx. 8 |

APPLICATION INFORMATION

| | |
|--------------------------------|--|
| Consumption | 1 litre for 7 to 10 m ² approx. |
| Ambient Air Temperature | Apply in dry weather conditions with at least 48 hours without rain after application. |

Substrate Temperature

Do not apply on the substrate during freezing or thawing.
Do not apply by too strong heat, on too hot substrate (>30°C risk of evaporation).

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Protect aluminium or painted steel joineries and gutters of houses. Rinse splashes and drips on lacquered joineries and gutters as quickly as possible with clean water.

APPLICATION

Preventive treatment:

Treat substrates in spring or autumn to avoid the proliferation of green stains.

Apply Sika® Stop GREEN directly without dilution onto the surface to be treated with a brush, roller or sponge mop or spray.

Do not rinse treated substrates after application.

Curative treatment:

Scratch and brush the areas where stains and residues are abundant.

Apply Sika® Stop GREEN directly without dilution and without excess onto the surface to be treated with the roller or sprayer until the surface to be treated is completely impregnated. Do not rinse treated substrates after application. Allow it to work - the green stains will turn black and will disappear over time.

Repeat the treatment if necessary for heavily affected areas.

CLEANING OF TOOLS

With water immediately after use.

LIMITATIONS

- Avoid run-off and contact with the soil, the waterways, drains and sewers.
- May be harmful to the environment if released in large quantities.
- Do not apply directly to lawns and plants.
- In case of recovery of water, do not use rainwater for watering gardens.
- Do not discard waste product into sewers, rivers or streams.
- Dispose of this material and its container in an appropriate hazardous waste facility.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland